

PRESS RELEASE

Vicon Rake Andex 784 – 844

02.09.2010, Gottmadingen, Germany



Andex 844

By adding many new features Vicon has started the generation change going from the -03 series to the new -04 series on its rake range. On the new models Andex 784 and 844 all these features are included and are leading to a higher capacity, better raking performance and easier operation.

Andex 784 – The Universal Machine

The new Andex 784 is a double rotor centre swath rake based on the main frame concept and the ProLine gear box technology. The machine offers an adjustable working width from 7.00 m up to 7.80 m and a corresponding swath width of 1.30 to 1.90 m. This makes the machine suitable to work in front of any kind of harvesting machine with narrow or wide pick ups. The working width adjustment can be done hydraulically from the tractor cab.

Andex 844 – The Professional Solution

The new Andex 844 is a double rotor centre swath rake based on the main frame concept and the ProLine gear box technology

The machine offers an adjustable working width from 7.60 m up to 8.40 m and a corresponding swath width of 1.40 to 2.00 m. This makes the machine suitable to work in front of any kind of harvesting machine with narrow or wide pick ups. The working width adjustment can be done hydraulically from the tractor cab.

Raking Performance and Operational Comfort

The ProLine rotor gear box is designed for very high loads and capacity under heavy working conditions. Maintenance free ball bearings on the tine arm control, 42 mm strong tine arms and 10 mm tine wire diameter ensure reliability and capacity.

The main frame and the rotor undercarriage of the machine have been redesigned and now provide an improved ground contour following under difficult circumstances.

Wheel sizes for the carrier frame up to 380/55-17 are available

In addition many details, such as tine arm storage position, height adjustment of the rotors, steering rods, working width/height indication, etc. have been improved in order to give maximum comfort to the user.

TerraLink Quattro Ground Contour Following

The unique key feature, which allows the rotors to adapt perfectly to any ground contours. It enables the rotor floating in 3 dimensions and gives a perfect raking result under all working conditions. In combination with the Quattro undercarriage which 4 wheels are running closest to the tines this system maximizes the possible working speed by at the same time ensuring clean and loss free raking. Soil contamination of the grass is minimized at the same time.

Technical Specifications:

	Andex 784	Andex 844
Working width	7.00 – 7.80 m,	7.60 – 8.40 m,
Transport height	3,30* / 4,10 m	3,45* / 4,10 m
Transport width	2,85 m	2,90 m
Tine arms per rotor	11	12
Tines per arm	4	4
Weight	1.750 kg	1.950 kg

* with detached tine arms

Kverneland Group (Kverneland ASA - OSE: KVE) is a leading international company developing, producing and distributing agricultural machinery and services. Strong focus on innovation allows us to provide a unique and broad product range with high quality. Kverneland Group offers an extensive package of systems and solutions to the professional farming community. The offering covers soil preparation, seeding, forage- and bale equipment, spreading and spraying. For more information on Kverneland Group visit www.kvernelandgroup.com

-- END --

For Details, Contact:

Uwe Kellermeier, Product Director, Mowers, Haytools & Wagons

Kverneland Group Gottmadingen

Tel. +49 7731 788 300

Email: uwe.kellermeier@kvernelandgroup.com